



TECHNICAL SPECIFICATION

	PA-400	PA-600	PA-800	PA-2400	PA-2800	PA-3600
Rated Power (Stereo 8Ω / ch.)	100W	150W	200W	300W	400W	500W
Rated Power (Stereo 4Ω / ch.)	150W	225W	300W	450W	600W	750W
Rated Power (Bridge Mono 8Ω)	300W	450W	600W	900W	1200W	1500W
Frequency Response	20Hz - 20KHz, -3dB @ 100KHz					
THD+N	< 0.03% @ 8Ω 1KHz					
S/N Ratio	> 90dB	> 90dB	> 95dB	> 102dB	> 102dB	> 102dB
Slew Rate	20V/us	20V/us	30V/us	40V/us	40V/us	40V/us
Damping Factor	> 400					
Crosstalk	> 65dB @ 8Ω 1KHz					
Input Impedance	20KΩ balanced / 10KΩ unbalanced					
Input Sensitivity	0.775V					
Class	Class AB					
Height	2U					

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoenakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897