

Specifications

	PK108A	PK110A
Amplifier		
Max output power	240 W*	320 W*
Type	Class-AB	
Loudspeaker System Data		
Woofer	8" (210 mm) LF driver	10" (255 mm) LF driver
Tweeter	1" (25.5 mm) HF compression driver	
Frequency response	20 Hz to 20 kHz (-10 dB)	
Sound pressure level (SPL)	Max. 90 dB	
Audio Connections		
MP3 Playback	USB / SD / TF	
File system	FAT 16, FAT 32	
Format	MP3 / WMA / WAV / FLAC / APE	
Bit rates	32 – 800 kbps	
Sample rates	44.1 kHz	
Input	1 x XLR / ¼" TRS combo jack	
Input impedance	20 kΩ balanced	
Line in	1 x ¼" (3.5 mm) TRS, stereo	
Input impedance	15 kΩ	
Aux in	2 x RCA	
Input impedance	15 kΩ, unbalanced	
Aux out	2 x RCA	
Output impedance	100 kΩ, unbalanced	
SD card slot		
Card memory	Up to 32 GB supported	
Bluetooth**		
Frequency range	2402 MHz ~ 2480 MHz	
Channel number	79	
Version	Bluetooth spec 5.0 compliant	
Compatibility	Supports A2DP 1.2 profile	
Max. communication range	10 m (without interference)	
Max. output power	10 dBm	
Equalizer		
High	±12 dB @ 10 kHz, shelving	
Low	±12 dB @ 100 Hz, shelving	
Power Supply, Voltage (Fuses)		
USA / Canada	120 V~, 60 Hz (F 2 A L 250 V)	
UK / Australia / Europe	220-240 V~, 50/60 Hz (F 1 A L 250 V)	
Korea / China	220-240 V~, 50 Hz (F 1 A L 250 V)	
Japan	100 V~, 50/60 Hz (F 2 A L 250 V)	
Power consumption	90 W	
Mains connection	Standard IEC receptacle	
Dimension / Weight		
Dimensions (H x W x D)	435 x 295 x 245 mm (17.13 x 11.61 x 9.65")	545 x 355 x 295 mm (21.46 x 13.97 x 11.61")
Weight	6.8 kg (14.9 lbs)	8.9 kg (19.6 lbs)