



NEW

ACS-1500 MK-II

Professional Active Column Speaker System

“ **เรียบง่าย**
แต่ **ทรงพลัง**
ดัง **พุง ครอบครัว** ”

“ **หยึดหยุน**
และ **ขยายได้**
รองรับพื้นที่ใช้งาน ”

แอมป์
Class D ในตัว

กำลังขับ **1800** วัตต์

DSP 5 โหมด
คุณภาพสูงจาก อเมริกา

- ✔ **DEFAULT**
- ✔ **MUSIC**
- ✔ **DANCE**
- ✔ **SPEECH**
- ✔ **USER**


(กำหนดค่าผ่าน Software ได้)

Bluetooth 5.0
รองรับ TWS

| ดอกลำโพง **Full Range**

เทคโนโลยีจาก อิตาลี
4 นิ้ว x **8** ดอก

ติดตั้ง **7** รูปแบบ
ได้สูงสุด



| ดอกลำโพง **Subwoofer**

ขนาดใหญ่ **15** นิ้ว

ข้อมูลสินค้าเพิ่มเติม





ACS-1500 MK-II

PROFESSIONAL ACTIVE COLUMN SPEAKER SYSTEM

ACS-1500 MK II Series Professional Active Column Speaker System which can cover the usage area from small to large Designed for hi-end professional sound performance especially for frequency response up to 40Hz ~ 18KHz \pm 3dB, Power maximum 1800 Watts Amplifier Class D with DSP processor 5 Preset for optimum performance. And can stream wireless music via TWS Bluetooth Support ideal lifesound concert, event, shopping mall, meeting room – training, fitness, restaurant, hotel banquet room.

This series includes ACS-1500S-MK II (subwoofer), ACS-1500C-MK II (column speaker)

FEATURE

- Subwoofer Component: 15", 3" voice coil
- Satellite Components: 4" X 8 Full Range Speaker
- Dispersion Angle (H x V): 80 x 20 Degree.
- Frequency response: 40Hz~18KHz \pm 3dB
- Max. SPL / (Peak): 125dB/134dB
- Power RMS: 900W / 1800W (MAX)
- Built-in Class D Amplifier
- Built-In DSP Processor Mode: DEFAULT , MUSIC , DANCE , SPEECH , USER
- Built-in Media player:TWS Bluetooth 5.0 (True Wireless Stereo)
- Operating voltage AC 220 - 240V, 50/60Hz

SPECIFICATIONS

Model	ACS-1500S-MK II (subwoofer)	ACS-1500C-MK II (column)
Transducer	Subwoofer Components : 15", 3" voice coil	Satellite Components : 4" X 8 Full Range Speaker
Frequency Response	40Hz ~ 180Hz \pm 3dB	180Hz ~ 18kHz \pm 3dB
Rated Power	600W / 1200W (MAX)	300W / 600W (MAX)
Amplifier	Class D	
Sensitivity	95dB 1m/1W	96dB 1m/1W
Maximum SPL	125dB/134dB (PEAK)	125dB/134dB (PEAK)
Nominal Impedance	4 Ω	4 Ω
Built-in DSP Processor	5 Mode Presets (DEFAULT, MUSIC, DANCE, SPEECH, USER)	
Media player	TWS Bluetooth 5.0 (True Wireless Stereo)	
Dispersion Angle (H x V)		80° X 20°
Connection		
Line Input	1 x Combo XLR or 1/4" Jack (female)	
Line Output	1 x XLR (male)	
Net Port	2 x RS485 (RJ45)	
Speaker Port	1 x Speakon (OUT)	1 x Speakon (in)
General		
Operating voltage	AC 220 ~ 240V, 50/60Hz	
Dimensions (H x W x D)	570 x 430 x 520mm	980 x 135 x 135mm
Net Weight	27 Kgs.	11 Kgs.



ACS-1500 MK-II